

SRS ViVA 1 topsynth alpha LA



Longlife High Performance Engine Oil

February 2019

Characteristics

SRS ViVA 1 topsynth alpha LA is a high performance low friction SAE 5W-30 engine oil with Low **SAPS** additive technology (low levels of Sulphated Ash, Phosphorus, Sulphur).

Selected base oils using synthetic technology and adapted innovative additives with reduced sulphated ash fulfil the demands of today's practice. Excellent cold start behaviour assures an optimal lubricant supply and high fuel economy at low temperatures.

SRS ViVA 1 topsynth alpha LA contributes to environmental protection through reduction of detrimental emissions. Extreme loads and high temperatures are controlled at all operating conditions.

Applications

SRS ViVA 1 topsynth alpha LA is especially recommended for diesel engines with emission reduction systems to fulfil the emission standards Euro IV. This engine oil adheres to the extended effectiveness of emission reduction systems. SRS ViVA 1 topsynth alpha LA is suitable for diesel as well as gasoline engines.

We recommend SRS ViVA 1 topsynth alpha LA for cars, too, where following specifications are required: Opel GM-LL-A-025 and Opel GM-LL-B-025. SRS ViVA 1 topsynth alpha LA meets Opel GM dexos2.

SRS ViVA 1 topsynth alpha LA can be used in gasoline and diesel engines, which require motor oils according to the earlier ACEA A3/B4.

Specifications

- SAE Grade 5W-30
- ACEA C3
- API SN/CF

Approvals

- MB-Approval 229.31
- MB-Approval 229.51
- MB-Approval 229.52
- VW-Norm 502 00 and 505 00
- VW-Norm 505 01

Recommendations

- Opel GM dexos2
- Ford WSS-M2C917-A
- BMW Longlife-04

SRS ViVA 1 topsynth alpha LA is a product of the H&R ChemPharm GmbH.

Typical Data	Test Method	SRS ViVA 1 topsynth alpha LA
SAE Grade	SAE J 300	5W-30
Density at 15°C	DIN 51 757	0.853
Dyn. Viscosity at -30°C (CCS)	ASTM D 5293	6,160
Kin. Viscosity at 40°C	DIN EN ISO 3104	68.8
Kin. Viscosity at 100°C	DIN EN ISO 3104	12.0
Viscosity Index (VI)	DIN ISO 2909	172
Flash Point COC	DIN ISO 2592	240
Pour Point	DIN ISO 3016	- 39
Total Base Number	DIN ISO 3771	7.2

The above values may vary within the commercial limits.

Made in Germany

