

SRS ViVA 1 special F top



Special High Performance Low Friction Engine Oil

February 2019

Characteristics

SRS ViVA 1 special F top is an extremely fuel-efficient high performance low friction 0W-30 engine oil based on modern synthetic technology.

Excellent low temperature flow characteristics protect optimal the engine during the cold starting. Extreme loads and high temperatures are safely handled under all operating conditions. It ensures very high wear protection and lower friction losses. SRS ViVA 1 special F top contributes through its high fuel economy and reduction of emissions to protect the environment.

Application

SRS ViVA 1 special F top is a top quality specially developed for the Ford specification WSS-M2C950-A in the new Ford TDCI Duratorq Euro 6 engines (from 2014) with exhaust aftertreatment and turbocharged ones.

SRS ViVA 1 special F top can be used up to 30,000 km at extended intervals, but is not backwards compatible with older Ford specifications. The specifications and regulations of the vehicle manufacturers must be observed.

SRS ViVA 1 special F top can also be used in engines, where ACEA A5/B5 is required.

Specification

- SAE Grade 0W-30
- ACEA C2

Recommendations

- Ford WSS-M2C950-A
- Fiat 9.55535-GS1/DS1

SRS ViVA 1 special F top is a product of the H&R ChemPharm GmbH.

Typical Data	Test Method	SRS ViVA 1 special F top
SAE Grade	SAE J 300	0W-30
Density at 15°C	DIN 51 757	0.847
Dyn. Viscosity at -30°C (CCS)	ASTM D 5293	5,710
Kin. Viscosity at 40°C	DIN EN ISO 3104	49.6
Kin. Viscosity at 100°C	DIN EN ISO 3104	9.58
Viscosity Index (VI)	DIN ISO 2909	181
Flash Point COC	DIN ISO 2592	234
Pour Point	DIN ISO 3016	-45
Total Base Number	DIN ISO 3771	8.0

The above values may vary within the commercial limits.

Made in Germany

