

SRS ViVA 1 topsynth 5W-30



Synthetic High Performance Low Friction Engine Oil

May 2013

Characteristics

SRS ViVA 1 topsynth 5W-30 is a synthetic high performance low friction SAE 5W-30 engine oil. Synthetic base oils components and adapted innovative additives ensure that the demands of today's practice are met.

Application

SRS ViVA 1 topsynth 5W-30 is suitable as a high performance low friction engine oil for use in sophisticated new generation engines. It is recommended for all passenger car gasoline and diesel engines, including the turbocharged and direct injected engines under all operating conditions.

Performance / Specifications

SRS ViVA1 topsynth 5W-30 satisfies the requirements for engine oils in accordance with

- SAE Grade 5W-30
- ACEA A3/B4
- API SN/CF
- MB-Sheet 229.3
- VW-Norm 502 00 and 505 00
- Porsche A40
- BMW Longlife-01

SRS ViVA 1 topsynth 5W-30 is a product of the H&R ChemPharm GmbH. Made in Germany.

Typical Data		Test Method	SRS ViVA 1 topsynth 5W-30
SAE Grade		SAE J 300	5W-30
Density at 15°C	g/cm ³	DIN 51 757	0.857
Dyn. Viscosity at -30°C (CCS)	mPa s	ASTM D 5293	5.950
Kin. Viscosity at 40°C	mm ² /s	DIN EN ISO 3104	69.2
Kin. Viscosity at 100°C	mm ² /s	DIN EN ISO 3104	11.9
Viscosity Index (VI)		DIN ISO 2909	168
Flash Point COC		DIN ISO 2592	228
Pour Point		DIN ISO 3016	-33
Total Base Number		DIN ISO 3771	9.85
Sulphated Ash		DIN 51 575	1.2

The above values may vary within the commercial limits.

Made in Germany